



T2™ TECHNOLOGY HACKSAW BLADES

T2™ TECHNOLOGY

Blade design delivers up to 2X longer blade life versus the prior generation of LENOX hacksaw blades

SHATTER RESISTANT

Bi-Metal construction allows blades to bend and flex without breaking



TPI	LENGTH X WIDTH		1-PACK	2-PACK	10-PACK	100-PACK	APPLICATION
	IN	MM	PROD NO	PROD NO	PROD NO	PROD NO	
14	12 X 1/2	300 X 12.7	—	—	20143V214HE	—	Wood and Metal
18	10 X 1/2	254 X 12.7	—	20163T018HE	20140V018HE	—	Heavy Metal
18	12 X 1/2	300 X 12.7	20154S218HE	20160T218HE	20144V218HE	20116218HE	Heavy Metal
24	10 X 1/2	254 X 12.7	20151S024HE	23930T024HE	20141V024HE	20111024HE	Medium Metal
24	12 X 1/2	300 X 12.7	20155S224HE	20161T224HE	20145V224HE	20117224HE	Medium Metal
32	10 X 1/2	254 X 12.7	—	20164T032HE	20142V032HE	—	Thin Metal
32	12 X 1/2	300 X 12.7	20156S232HE	20162T232HE	20146V232HE	20118232HE	Thin Metal

HIGH TENSION HACKSAW

50,000 PSI

HIGH BLADE TENSION

Unique I-Beam construction allows blade to tension up to 50,000 psi, resulting in fast, straight cuts

COMFORTABLE GRIPS

Rubberized handles allow for confident handling even in wet or cold environments

CONVERT TO A JAB SAW

Accepts any LENOX reciprocating saw blade to be used as a jab saw

CONVENIENT BLADE STORAGE

Store up to 5 extra 12" hacksaw blades in the I-Frame



PROD NO	BLADE SPECIFICATION
12132HT50	12" (305 mm) 24TPI Hacksaw Blade



Tensioning Mechanism



Use as a Jab Saw



Stores up to 5 Blades in I-Frame



Comfortable Grips