

PVC Condensate Pipe



PRODUCT

PVC Condensate Pipe

APPLICATION

Condensate Management for residential, industrial, agricultural

PURPOSE

Our PVC condensate pipes are designed to meet the needs for residential commercial applications. Smooth inner walls allow for low pressure drops and resistance to chemicals and corrosion.

ADVANTAGES

Our PVC Pipe product line is manufactured to meet the needs of residential, commercial, & industrial plumbing systems, and other pressure applications. With top quality raw materials and modern processing technology, our PVC pipe meets industry standards in addition to our own rigorous quality control standards.

For sizes 1 1/4" and larger, our Schedule 40 pipe is also dual rated to ASTM D2665 for DWV applications. This gives the designer, installer, and end user the flexibility of one product for two distinct applications.

GENERAL CHARACTERISTICS

- Maximum Temperature 140°F
- PVC Material
- Sold by the Pallet
- 1 Year Warranty

| ITEM # | Type | Length | Pressure Rating | Nominal Size | Min Wall Thickness | Outside Diameter | Bell Depth |
|----------|-------------|--------|-----------------|--------------|--------------------|------------------|------------|
| 5-401-P | Schedule 40 | 10 ft | 480 psi | 3/4 in | 0.133 in | 1.050 in | 2.500 in |
| 5-404-P | Schedule 40 | 10 ft | 280 psi | 2 in | 0.154 in | 2.375 in | 3.250 in |
| 5-405-P | Schedule 40 | 10 ft | 260 psi | 3 in | 0.216 in | 3.500 in | 4.250 in |
| 5-407-P | Schedule 40 | 20 ft | 480 psi | 3/4 in | 0.113 in | 1.050 in | 2.500 in |
| 5-416-P | Schedule 40 | 20 ft | 450 psi | 1 in | 0.133 in | 1.315 in | 2.500 in |
| 5-417-P | Schedule 40 | 20 ft | 370 psi | 1 1/4 in | 0.140 in | 1.660 in | 2.500 in |
| 5-418-P | Schedule 40 | 20 ft | 330 psi | 1 1/2 in | 0.145 in | 1.900 in | 2.500 in |
| 5-2002-P | SDR 21 | 10 ft | 200 psi | 3/4 in | 0.060 in | 1.050 in | 2.500 in |
| 5-2005-P | SDR 21 | 20 ft | 200 psi | 3/4 in | 0.060 in | 1.050 in | 2.500 in |