

LENOX® LUMBERWOLF™ RECIPROCATING SAW BLADES

CUT THROUGH WOOD WITH NAILS WITH EASE

Blade thickness and profile are ideal for cutting through dense wood with nails



PLUNGE CUT WITH EASE

Blade tip designed for easy, quick, and clean plunge cutting



**For LENOX blades with this feature, refer to product packaging or go to www.lenoxtools.com
Applies to LUMBERWOLF™ blade models except for 634R and 676RC.



RELIABLY AGGRESSIVE CUTTING

High-speed steel cutting edge and spring steel backing helps strengthen the blade, reduce breaks, and provides durability for long blade life

| TPI | LENGTH X WIDTH X THICKNESS | | 1-PACK | 5-PACK | 25-PACK | 50-PACK | RAPID PLUNGE | APPLICATION |
|-----|----------------------------|----------------|------------|------------|------------|--------------|--------------|--------------------|
| | IN | MM | PROD NO | PROD NO | PROD NO | PROD NO | | |
| 4 | 4 X 3/4 X .050 | 102 X 19 X 1.3 | 20574S634R | 20575634R | - | - | - | Fast Wood |
| 6 | 6 X 7/16 X .050 | 152 X 11 X 1.3 | - | 20556676RC | - | - | - | Nail-Embedded Wood |
| 6 | 6 X 3/4 X .050 | 152 X 19 X 1.3 | 20573S656R | 20572656R | 20530B656R | 227500SB656R | ** | Nail-Embedded Wood |
| 6 | 9 X 3/4 X .050 | 229 X 19 X 1.3 | 20587S956R | 20582956R | 20558B956R | 227520SB956R | ** | Nail-Embedded Wood |
| 6 | 12 X 3/4 X .050 | 305 X 19 X 1.3 | 20586S156R | 20585156R | 20495B156R | 227550SB156R | ** | Nail-Embedded Wood |

BI-METAL CONSTRUCTION

Durable and flexible to survive nail strikes

FLEAM GROUND TOOTH FORM

Fast, clean wood cutting



IDEAL FOR CLEAN WOOD, PLASTIC PIPE AND TREE PRUNING

| TPI | LENGTH X WIDTH X THICKNESS | | 5-PACK | APPLICATION |
|-----|----------------------------|----------------|-------------|-------------------------------|
| | IN | MM | PROD NO | |
| 6 | 6 X 3/4 X .050 | 152 X 19 X 1.3 | 121016W6R | Clean Wood, Plastics, Pruning |
| 6 | 8 X 3/4 X .050 | 229 X 19 X 1.3 | 121029W6R | Clean Wood, Plastics, Pruning |
| 6 | 6 X 3/4 X .050 | 152 X 19 X 1.3 | 20570636RP* | Drywall/Plaster |

*Blade does not have fleam ground toothform

LENOX DIAMOND™ & CARBIDE GRIT RECIPROCATING SAW BLADES

LASTS LONGER

Nickel alloy-brazed lab-made diamond particles maintain sharpness to keep cutting after conventional carbide grit blades fail



STRAIGHT, CLEAN CUTS

Unlike bulky snap cutters which crush pipes and leave ragged, uneven cuts, LENOX DIAMOND™ cuts clean. Durable chrome alloy backing steel provides extra stability



| LENGTH X WIDTH X THICKNESS | | 1-PACK | APPLICATION |
|----------------------------|-----------------|-------------|--|
| IN | MM | PROD NO | |
| 8 X 3/4 X .040 | 203 X 19 X 1.00 | 10833800RDG | Cast Iron, Tile, Brick and Natural Stone |
| 9 X 3/4 X .042 | 225 X 19 X 1.07 | 1766338 | Cast Iron, Tile, Brick and Natural Stone |
| 11 X 3/4 X .042 | 275 X 19 X 1.07 | 1766356 | Cast Iron, Tile, Brick and Natural Stone |

HIGH PERFORMANCE IN ABRASIVE MATERIALS

Cuts through tough materials that resist chip-forming, including ceramics, pipe, man-made stone, brick, marble and more

SMOOTH, QUICK CUTS

Uniformly applied, durable carbide grit particles on a flexible blade provide quicker cuts without snagging or binding



| LENGTH X WIDTH X THICKNESS | | 1-PACK | GRIT | APPLICATION |
|----------------------------|----------------|------------|--------|--|
| IN | MM | PROD NO | | |
| 6 X 3/4 X .032 | 152 X 19 X .8 | 20505600RG | MEDIUM | Fiberglass, Ceramic, Tile, Cultured Marble, Clays, Brick |
| 8 X 3/4 X .040 | 203 X 19 X 1 | 20576800RG | MEDIUM | Fiberglass, Ceramic, Tile, Cultured Marble, Clays, Brick |
| 10 X 3/4 X .050 | 254 X 19 X 1.3 | 20506100RG | MEDIUM | Fiberglass, Ceramic, Tile, Cultured Marble, Clays, Brick |

†This blade uses manufactured nickel alloy-brazed lab-made diamond particles engineered for cutting