

TEMPERATURE LIMIT CONTROL SWITCHES



LIMIT CONTROL SWITCHES - AUTO RESET


Limit Control Switches - Auto Reset (Large Flanged Airstream - 60T) - CONTINUED

THERMODISC

PART NO	TOD SWITCH SERIES	OPEN TEMP (°F)	TOLERANCE OPEN TEMP (°F)	CLOSE TEMP (°F)	TOLERANCE CLOSE TEMP (°F)	NOM TEMP Difference	MAX Voltage Rating (VAC)	MAX Current Rating (A)	COLOR CODE	DISC FACE	SWITCH TYPE	CONTACT ORIENT	MOUNTING INSERTION DEPTH-MAX (IN)
47-25117-02	60T	170	+/-5	130	+/-7	40	230	25	_	Enclosed	SPST	Normally Closed	3/8
47-25261-16	60T	170	+/-5	130	+/-9	40	230	25	_	Enclosed	SPST	Normally Closed	3/8
47-23610-21	60T	175	+/-5	155	+/-5	20	230	25	Red/White	Enclosed	SPST	Normally Closed	25/32
47-23113-08	60T	180	+/-6	100	+/-8	80	230	25	Blue	Enclosed	SPST	Normally Closed	3/8
47-23113-02	60T	180	+/-6	100	+/-8	80	230	25	Blue	Enclosed	SPST	Normally Closed	3/8
PD470041	60T	180	+/-5	135	+/-7	45	230	25	_	Exposed	SPST	Normally Closed	3/8
47-19554-89	60T	180	+/-5	140	+/-8	40	230	25	Red	Enclosed	SPST	Normally Closed	3/8
PD476605	60T	180	+/-5	140	+/-5	40	230	25	Red	Enclosed	SPST	Normally Closed	3/8
47-25117-03	60T	180	+/-5	140	+/-7	40	230	25	_	Enclosed	SPST	Normally Closed	3/8
47-23113-07	60T	180	+/-5	150	+/-6	30	230	25	Green	Enclosed	SPST	Normally Closed	3/8
47-23113-01	60T	180	+/-5	150	+/-6	30	230	25	Green	Enclosed	SPST	Normally Closed	3/8
47-23610-25	60T	185	+/-5	165	+/-5	20	230	25	Pink/White	Enclosed	SPST	Normally Closed	25/32
47-23113-10	60T	190	+/-6	110	+/-8	80	230	25	Red	Enclosed	SPST	Normally Closed	3/8
47-23113-05	60T	190	+/-6	110	+/-8	80	230	25	Red	Enclosed	SPST	Normally Closed	3/8
PD470040	60T	190	+/-5	145	+/-7	45	230	25	_	Exposed	SPST	Normally Closed	3/8
47-23113-03	60T	190	+/-5	150	+/-7	40	230	25	Yellow	Enclosed	SPST	Normally Closed	3/8
47-25117-04	60T	190	+/-5	150	+/-7	40	230	25	_	Enclosed	SPST	Normally Closed	3/8
47-23610-27	60T	190	+/-5	170	+/-5	20	230	25	Orange/White	e Enclosed	SPST	Normally Closed	25/32
47-23113-09	60T	200	+/-6	120	+/-8	80	230	25	White	Enclosed	SPST	Normally Closed	3/8
47-23113-04	60T	200	+/-6	120	+/-8	80	230	25	White	Enclosed	SPST	Normally Closed	3/8
47-19554-41	60T	200	+/-6	120	+/-8	80	230	25	White	Enclosed	SPST	Normally Closed	3/8
47-19554-45	60T	200	+/-5	160	+/-7	40	230	25	Red	Enclosed	SPST	Normally Closed	3/8
47-25117-05	60T	200	+/-5	160	+/-7	40	230	25	_	Enclosed	SPST	Normally Closed	3/8
47-17359-30	60T	200	+/-5	180	+/-5	20	230	25	Red	Enclosed	SPST	Normally Closed	3/8
47-23610-23	60T	200	+/-5	180	+/-5	20	230	25	Green/White	Enclosed	SPST	Normally Closed	25/32
PD476608	60T	210	+/-6	165	+/-8	45	230	25		Enclosed	SPST	Normally Closed	3/8
47-23610-29	60T	210	+/-5	190	+/-5	20	230	25	Violet/White	Enclosed	SPST	Normally Closed	25/32
47-23113-06	60T	215	+/-7	135	+/-9	80	230	25	Orange	Enclosed	SPST	Normally Closed	3/8







THERMODISC

PART NO	TOD SWITCH SERIES	OPEN TEMP (°F)	TOLERANCE OPEN TEMP (°F)	CLOSE TEMP (°F)	TOLERANCE CLOSE TEMP (°F)	NOM Temp Difference	MAX Voltage Rating (VAC)	MAX Current Rating (A)	COLOR CODE	DISC FACE	SWITCH Type	CONTACT ORIENT	MOUNTING INSERTION DEPTH-MAX (IN)
47-102436-07	44T	100	+/-8	80	+/-9	20	26	1	Brown	Enclosed	SPST	Normally Closed	3/8
47-102436-06	44T	110	+/-8	90	+/-9	20	26	1	Purple	Enclosed	SPST	Normally Closed	3/8
47-102436-04	44T	115	+/-8	95	+/-9	20	26	1	Red	Enclosed	SPST	Normally Closed	3/8
470015	44T	120	+/-8	100	+/-9	20	26	1	Yellow	Enclosed	SPST	Normally Closed	3/8
47-102436-03	44T	125	+/-8	105	+/-9	20	26	1	Blue	Enclosed	SPST	Normally Closed	3/8
47-102436-08	44T	130	+/-8	110	+/-9	20	26	1	Black	Enclosed	SPST	Normally Closed	3/8
47-102436-05	44T	135	+/-8	115	+/-9	20	26	1	Green	Enclosed	SPST	Normally Closed	3/8
470018	44T	145	+/-8	125	+/-9	20	26	1	Orange	Enclosed	SPST	Normally Closed	3/8